

# ***Cross Comparison of Meteorological Sensors***

***Pradeep K. Thapliyal***

**Space Applications Centre (ISRO)  
Ahmedabad (INDIA)**

***pkthapliyal@sac.isro.gov.in***

# Objective

- Inter-calibration of satellite measured radiances from diverse range of satellite instruments is important to make the observations consistent to produce globally homogenous products for environmental monitoring
- Proxy radiance generation (IR Imager/Sounder) for the verification of retrieval algorithm for future satellite sensors and system definition studies.
- **Presentation summarizes :**
  - **Inter-calibration of Indian geostationary satellites INSAT-3A, Kalpana and INSAT-3D Imager and Sounder channels with Hyperspectral sounder observations from IASI and AIRS.**
  - **Proxy radiance generation for INSAT-3D and verification with GOES-13.**

# Indian Geostationary Met Satellites/Sensors

Kalpana : VHRR (WV and TIR channels)

INSAT-3A : VHRR (WV and TIR channels)

INSAT-3D (Launch - First quarter of 2013):

Imager (6 Channels – VIS, SWIR, MWIR, WV, TIR1, TIR2)

Sounder (18 IR + 1 Vis Channels)

GISAT (design stage): Hyperspectral Vis, NIR, SWIR

Multispectral IR (6 channels, 1.5 km spatial resolution)

# Meteorological Products



<http://www.mosdac.gov.in>






Kalpana /INSAT-3A

- Atmospheric Wind Vectors (AMV)
- Outgoing Longwave Radiation (OLR)
- Upper Tropospheric Humidity (UTH)

INSAT-3D Imager: AMV, OLR, UTH, SST


Sounder: T, q profiles, total column Ozone

# Sample Kalpana products (IMDPS) (30 minutes interval)










**KALPANA-1 OLR ( $W/m^2$ ) 07OCT2010 08:00 Z**



**KALPANA-1 UTH (%) 07OCT2010 08:00 Z**




**KALPANA-1 QPE (mm,  $1^\circ \times 1^\circ$ ) 07OCT2010 08:00 Z**



# Inter-calibration of Kalpana

- Launched in Sep 2002
- Positioned at 74°E.
- Full disk every 30 minutes
- VHRR
  - VIS : 0.55-0.75  $\mu\text{m}$
  - WV : 5.7-7.1  $\mu\text{m}$
  - TIR : 10.5-12.5  $\mu\text{m}$
- Spatial resolution (at nadir) :
  - 2 km for VIS
  - 8 km for WV and TIR channels



# Aqua-AIRS and Metop-IASI spectral coverage with Kalpana SRFs for TIR and WV channels



**AIRS:** Atmospheric InfraRed Sounder

Polar Orbiting Aqua (2002)

**Channels:** 2378 ( $650\text{ cm}^{-1}$  to  $2675\text{ cm}^{-1}$ )  
( $3.74\text{ }\mu\text{m}$  -  $15.4\text{ }\mu\text{m}$ )

**Spectral resolution:**  $\nu/\Delta\nu \approx 1200$

**Spatial Resolution:** 13.5 Km at Nadir



**IASI:** Infrared Atmospheric Sounding  
Interferometer (Polar Orbiting Metop-A, 2007)

**Channels:** 8461 ( $645\text{ cm}^{-1}$  to  $2760\text{ cm}^{-1}$ )  
( $3.62\text{ }\mu\text{m}$  -  $15.5\text{ }\mu\text{m}$ )

**Spectral resolution:**  $0.35\text{ cm}^{-1}$  at SWIR  
 $0.50\text{ cm}^{-1}$  at LWIR  
(resampled at  $0.25\text{ cm}^{-1}$ )

**Spatial Resolution:**  $\sim 12\text{ km}$  at Nadir



# Inter-calibration Procedure

- Convolved radiance of broadband sensor using hyperspectral sounders:

$$R_{conv} = [\sum_{i=1}^n R_{AIRS}^i S_{Kalp}^i \Delta \nu] / [\sum_{i=1}^n S_{Kalp}^i \Delta \nu]$$

- $S_{Kalp}$  is Kalpana SRF at the central wavenumber of hyper-spectral channel,
- Missing or bad channels are interpolated from nearest 2 channels.
- Conversion of radiances to brightness temperature by inverting the equivalent Planck's function:


$$R_{conv} = \frac{2hc^2\nu^3}{\exp\{hc\nu / k(a_1 + a_2T_b)\} - 1}$$

- $a_1$  (=1.052K) and  $a_2$  (=0.996) are the band correction coefficients and  $\nu$  (=885.602 cm<sup>-1</sup>) is central wavenumber for Kalpana TIR channel





# Inter-calibration Procedure...

## Data Source: Metop-IASI L1C (Eumetcast, BUFR format)

- Land/sea mask: Use only ocean pixels
- Temporal Collocation: 15 Minutes
- Spatial Collocation: Within IASI IFOV (2x2 pixels)
- Zenith angle collocation:  
 $|\sec(\beta_{IASI}) - \sec(\beta_{Kalp})| < 0.01$   
 $\beta_{IASI} \& \beta_{Kalpana} < 10^\circ$
- Spatial homogeneity test:  
(Std. Dev. of Kalpana Tb within one IASI IFOV) /  
(mean Tb of Kalpana within one IASI IFOV) < 0.01



# Procedure testing with Meteosat-7



**Meteosat-7 vs IASI convolved**  
**01 June 2011, 0230 GMT**





**EUMETSAT - GSICS**  
**webpage for Meteosat-7**  
**vs IASI intercalibration**



# Intercalibration of Kalpana with IASI


## Kalpana TIR Channel vs Metop-IASI Convolved

## Kalpana WV Channel vs Metop-IASI Convolved







(a) TIR Channel/Ascending




(b) TIR Channel/Descending




(a) WV Channel/Ascending





(b) WV Channel/Descending



# Intercalibration of Kalpana with Aqua-AIRS for 2009




- Only for clear sky ( $T_b > 280K$ )
- Small Std. Dev.: 0.3-0.4 K
- Bias smaller during daytime with seasonal variations
- Bias higher during nighttime




# Proxy radiance generation for INSAT-3D Sounder Algorithm testing

- Extend the Intercalibration methodology to generate proxy radiances for future satellite Imager/Sounder
- Testing the procedure with existing satellites (GOES)
- Bias correction (slope/offset) using data from similar existing satellite sensors or line-by-line radiative transfer model


3DSND 01JUL2012 0220 01




3DSND 01JUL2012 0220 02




3DSND 01JUL2012 0220 03




3DSND 01JUL2012 0220 04




3DSND 01JUL2012 0220 05




3DSND 01JUL2012 0220 06





3DSND 01JUL2012 0220 07



3DSND 01JUL2012 0220 08




3DSND 01JUL2012 0220 09




14-bit count




3DSND 01JUL2012 0220 10




3DSND 01JUL2012 0220 11




3DSND 01JUL2012 0220 12




3DSND 01JUL2012 0220 13




3DSND 01JUL2012 0220 14




3DSND 01JUL2012 0220 15





3DSND 01JUL2012 0220 16



3DSND 01JUL2012 0220 17




3DSND 01JUL2012 0220 18



14-bit count


# Proxy Radiance for INSAT-3D using IASI

## (Test with GOES-13)





# Radiance bias correction for INSAT-3D



# Future plans

- Intercalibration of Kalpana/INSAT-3A TIR and WV channels for entire period with Aqua-AIRS and Metop-IASI.
- Website (MOSDAC) to provide time series of the bias and Std. Dev. alongwith the GSICS correction coefficients.
- Application of proxy radiances for testing the algorithms for future satellites and system definition studies for new sensors.



***Thank You***